

FIG. 1 is a block diagram of a system for inserting electronic watermark data into an image. The system includes an original image (101) which is converted to DCT (103) and then quantized (104). A movement decision unit (106) and a picture-type decision section (107) are used to determine the appropriate watermark data to insert. The watermark data is then inserted (105) and the resulting image is converted back to the original format (111) and compressed (113) to produce the final image with inserted electronic watermark data (112).

FIG. 1





FIG. 2





FIG. 3



4
G.
L




FIG. 5




FIG. 6





FIG. 7



A diagram showing a grid of frequency values. The horizontal axis is labeled 'HORIZONTAL SPACE FREQUENCY fH' with an arrow pointing right. The vertical axis is labeled 'VERTICAL SPACE FREQUENCY fV' with an arrow pointing down. The grid contains 8 rows and 8 columns of cells, each containing a number. The numbers are arranged in a specific pattern: the first row contains 1, 2, 6, 7, 15, 16, 28, 29; the second row contains 3, 5, 8, 14, 17, 27, 30, 43; the third row contains 4, 9, 13, 18, 26, 31, 42, 44; the fourth row contains 10, 12, 19, 25, 32, 41, 45, 54; the fifth row contains 11, 20, 24, 33, 40, 46, 53, 55; the sixth row contains 21, 23, 34, 39, 47, 52, 56, 61; the seventh row contains 22, 35, 38, 48, 51, 57, 60, 62; and the eighth row contains 36, 37, 49, 50, 58, 59, 63, 64.

	1	2	6	7	15	16	28	29
3	3	5	8	14	17	27	30	43
4	4	9	13	18	26	31	42	44
10	10	12	19	25	32	41	45	54
11	11	20	24	33	40	46	53	55
21	21	23	34	39	47	52	56	61
22	22	35	38	48	51	57	60	62
36	36	37	49	50	58	59	63	64

FIG. 8




FIG. 9
PRIOR ART




FIG. 10
PRIOR ART

